



## Investigation of Heat Transfer Characteristics of Spherical Copper and Alumina Nanoparticles in Water and Ethylene glycol Based Fluids

**Ngiangia AT, Nwabuzor PO**

Department of Physics, University of Port Harcourt, P M B 5323 Choba, Port Harcourt, Nigeria

### Article History

Received: 21 November 2020

Reviewed & Revised: 22/November/2020 to 22/December/2020

Accepted: 23 December 2020

E-publication: January 2021

### Citation

Ngiangia AT, Nwabuzor PO. Investigation of Heat Transfer Characteristics of Spherical Copper and Alumina Nanoparticles in Water and Ethylene glycol Based Fluids. *Indian Journal of Engineering*, 2021, 18(49), 13-30

### Publication License



This work is licensed under a Creative Commons Attribution 4.0 International License.

### General Note

 Article is recommended to print as color digital version in recycled paper.

### ABSTRACT

A study of heat transfer rate of spherical copper and alumina nanoparticles in water and ethylene glycol based fluids was carried out. A modified thermal conductivity model in conjunction with steady state momentum and energy equations in spherical coordinates were put into dimensionless form and solutions used to determine the skin friction, heat transfer coefficient and thermal conductivity as well as viscosity. The modified model incorporates Brownian motion and varied sphericity to observe the effect of temperature and other material parameters on the velocity and temperature profiles of the fluid. Using numerical values, it was shown that the nanoparticle volume fractions, the diameter and Prandtl number, not only enhanced the thermal conductivity of nanofluids but also the velocity and temperature profiles. It was also observed that the Brownian motion which is temperature dependent was actually a weak factor in enhancement of thermal conductivity. The effect of other parameters as well as calculation of mass flux and mean temperature was determined.

**Keywords:** Heat transfer rate, Spherical coordinates, Copper, Alumina, Water, Ethylene glycol, Nanofluids.

## 1. INTRODUCTION

Generally, nanofluids are formed when some quantity of nanoparticles and base fluids are mixed. The nanoparticles has an average diameter between 1nm to 100nm. The nanoparticles are mainly oxides, metals and carbides while the common base fluids are water, ethylene glycol and other traditional heat transfer fluids. Nanofluids exhibit enhanced properties when compared to conventional heat transfer fluids and other metallic nanoparticles. The larger relative surface area of nanoparticles, compared to those of conventional particles, appears to justify significantly the enhanced heat transfer capabilities and also should improve the stability of the suspensions. Also, nanofluids enhanced abrasion-related properties as compared to the conventional solid/liquid mixtures. Successful use of nanofluids will support the component miniaturization by enabling the design and production of smaller and lighter heat exchanger systems. In his pioneer work, Choi [1], described the mixture as nanofluid with increased thermal conductivity of the base fluids and their convective heat transfer rate. The mixture or nanofluid when compared to the base fluid, it is observed that changes occur in viscosity, thermal conductivity and density. Nanofluids can therefore be described as new class of enhanced heat transfer fluids formed as a result of dispersion of nanometer-size particles in base fluids. Of the basic physical properties of nanofluids, thermal conductivity is the most important due to its application in heat transfer. The enhanced heat transfer was established because; nanofluid thermal conductivity is a function of nanoparticle size, shape, volume fraction and spatial distribution. Others are base fluid type, temperature and pH value (Yu et al [2], Eapen et al [3]). Nanofluids uses are abounded in various electronic equipment, energy production, power generation and air conditioning and production. Serious study in convective heat transfer using suspensions of nanometer-size particles in a chosen base fluid started only over the past decade. The study is either experimental or theoretical and a combination of both. Koblinski et al.[4], in a study, outline and examined the properties of nanofluids and future challenges. In spite of the several successes made, the research and development of nanofluids is seen as rapid but still hindered by several factors such as the lack of agreement between experimental and theoretical results, poor characterization of suspensions, and the lack of theoretical understanding of the mechanisms. This trend rather increased the study of naofluids and its applications. According to some proposed classical nanofluid models (Xie et al [5], Hamilton and Crosser [6], Jeffrey [7], Davis [8], Wang et al [9], Koo et al [10], Jang and Choi [11]), effective thermal conductivity of mixtures can be calculated and other parameters of the system also determined. However, results of some researches (Patel et al [12], Das et al [13], Xuan et al [14], Kumar et al [15], Bhattacharya et al [16], Putnam et al [17], Koo and Kleinstreuer [18 and 19]) strongly argued that the non inclusion of Brownian motion effect which is temperature dependent to the earlier stated models is a minus and therefore not a holistic approach to the determination of thermal conductivity enhancement, hence their studies. Surprisingly, Wang et al [20], in their study, declared that the effective thermal conductivity enhancement due to Brownian motion is not necessary. The implication is that the effect of temperature on the enhancement of thermal conductivity is very minimal and can be discarded. Koblinski [21], opined that the heat transferred by nanoparticle diffusion contributes minimally to thermal conductivity enhancement. In all, errors arising from preparation of nanofluids include, heating and measurement processes and cleanliness of apparatus are some of experimental results differences in the various studies while over simplification and assumption of certain parameters are the causes of some classical models. As a result of these uncertainties, some of the results appear to be conflicting. The aim of this study is to include Brownian motion into our proposed model which is a modification of the classical models of nanofluids of Koo and Kleinstreuer ([18 and 19]). By this modification, different sphericities for different shapes nanoparticles in addition to other consideration which is an extension are made.

### Formalism

A steady boundary layer flow of viscous, incompressible, Newtonian Spherical nanofluid is considered. Using the Boussineq's approximation, the governing equations of the nanofluid in steady spherical coordinate is given as

$$\frac{\mu_{nf}}{\rho_{nf}} \left( \frac{2v_r}{r'^2} + \frac{4}{r'} \frac{\partial v_r}{\partial r'} + \frac{\partial^2 v_r}{\partial r'^2} \right) + g\beta_{nf}(T - T_0) = 0 \quad (1)$$

$$\frac{k_{nf}}{(\rho C_p)_{nf}} \left( \frac{2}{r'} \frac{\partial T}{\partial r'} + \frac{\partial^2 T}{\partial r'^2} \right) = 0 \quad (2)$$

Subject to the boundary conditions (Wang et al, [9])



$$\begin{aligned} v_r|_{r'=R} &= v_0 \\ v_r|_{r'=0} &= v_0 \end{aligned} \quad (3)$$

$$\begin{aligned} T|_{r'=R} &= T_w \\ T|_{r'=0} &= T_0 \end{aligned} \quad (4)$$

where  $v_r$  is nanofluid velocity,  $v_0$  is characteristic velocity,  $r$  is radius of nanoparticles,  $T$  is temperature of nanofluid,  $T_0$  is characteristic temperature,  $T_w$  is ambient temperature and  $g$  is acceleration due to gravity.

In this work, according to Hamilton and Crosser model [6], effective dynamic viscosity ratio and effective thermal conductivity ratio which are valid for both spherical and non spherical shapes nanoparticles are stated as

$$\frac{\mu_{nf}}{\mu_f} = (1 + a\phi + b\phi^2) \quad (5)$$

$$\frac{k_{nf}}{k_f} = \frac{k_s + (n-1)k_f + (n-1)(k_s - k_f)\phi}{k_s + (n-1)k_f - (k_s - k_f)\phi} \quad (6)$$

The  $n$  is the empirical shape factor given by  $n = \frac{3}{\psi}$  where  $\psi$  is the sphericity.

According to the work of Tiwari and Das [22] and Asma et al [23], density of nanofluid ( $\rho_{nf}$ ), thermal expansion due to temperature of nanofluid ( $\beta_{nf}$ ), specific heat at constant pressure of nanofluid are respectively

$$\begin{aligned} \rho_{nf} &= (1 - \phi)\rho_f + \phi\rho_s \\ \beta_{nf} &= (1 - \phi)\beta_f + \phi\beta_s \\ (C_p)_{nf} &= (1 - \phi)(C_p)_f + \phi(C_p)_s \end{aligned} \quad (7)$$

where  $\phi$  is the nanoparticles volume fractions given by  $\phi = \frac{v_s}{v_f + v_s} = m \frac{\pi}{6} D_s^3$ ,  $m$  is the number of particles per unit volume and  $D$  is the average diameter of the particles,  $\rho_f$  and  $\rho_s$  are the densities of the base fluid and solid nanoparticles,  $\beta_f$  and  $\beta_s$  are the thermal expansion due to temperature of base fluid and solid nanoparticles, and  $(C_p)_f$  and  $(C_p)_s$  are the specific heat at constant pressure due to base fluid and solid nanoparticles.  $a$  and  $b$  are constants that depend on the particle shape (Aaiza et al [24]). The thermo physical properties of alumina ( $Al_2O_3$ ) and copper ( $Cu$ ) nanoparticles as well as water ( $H_2O$ ) and ethylene glycol ( $C_2H_6O_2$ ) as base fluids are presented in table 3.

**Table 1:** Sphericity  $\psi$  and empirical shape factor for different shapes nanoparticles (Aaiza et al [24])

Model	Platelet	Blade	Cylinder	Brick
$\psi$	0.52	0.36	0.62	0.81
$n$	5.76923	8.33333	4.83871	3.70370

**Table 2:** Constants **a** and **b** empirical shape factors (Aaiza et al [24])

Model	Platelet	Blade	Cylinder	Brick
<b>a</b>	37.1	14.6	13.5	1.9
<b>b</b>	612.6	123.3	904.4	471.4

**Table 3:** Thermo physical properties of  $Al_2O_3$  and  $Cu$  nanoparticles,  $C_2H_6O_2$  and  $H_2O$  (Aaiza et al [24])

Property	$H_2O$	$C_2H_6O_2$	$Al_2O_3$	$Cu$
$(C_p)_{nf}$ (J/kgK)	4179	0.58	765	385
$\rho$ (kg/m <sup>3</sup> )	997.1	1.115	3970	8933
$k_{nf}$ (W/mk)	0.613	0.149	40	401
$\mu_{nf}$ (m <sup>2</sup> s <sup>-1</sup> )	0.00089	0.001095	0.0000029014	0.00046
$\beta \times 10^{-5}$ (k <sup>-1</sup> )	21	6.5	0.85	1.67

The Hamilton and Crosser model [6], shows that the effective thermal conductivity of nanofluids depends on the thermal conductivity of the spherical solid, the base fluid and the volume fraction of the solid parts. However, to effectively determine the thermal conductivity of nanofluids, Patel et al [12], observe that, the Brownian motion effect on nanoparticles at the molecular and nano-scale levels may be a key mechanism governing the thermal behaviour of nanofluids. In a similar experimental study conducted by Das et al [13], they find out that thermal conductivity of nanofluids depends strongly on temperature and that this fact should be considered in theoretical models. The Hamilton and Crosser model ignored Brownian motion which is temperature dependent; it is therefore defective in determining the effective thermal conductivity of nanofluids. In a related development, studies that incorporate Brownian motion were reported. Few of the works include Xuan et al [14], which included the Brownian motion into the model proposed but was criticized of being too weak in temperature dependence and also at variance with experimental data of Das et al [13]. Also, Kumar et al [15], proposed a model to account for the large enhancement of thermal conductivity of nanofluids and its strong temperature dependence, but its use showed that it is not suitable for high concentration of particles. Another study carried out by Bhattacharya et al [16], developed a technique to determine the effective conductivity of a nanofluid using Brownian motion simulation. Although the model showed good agreement with other works, its sphericity is just 1. The same issue of sphericity being 1 was the weak point of the model proposed by Putnam et al [17] which is a modification of Maxwell's model. Above all, Koo and Kleinstrever ([18 and 19]), proposed a model of nanofluids which among other factors included the effect of particle size, particle volume fraction, temperature and properties of the base fluid. The model is stated as

$$\frac{k_{nf}}{k_f} = \frac{k_s + 2k_f + 2(k_s - k_f)\phi}{k_s + 2k_f - (k_s - k_f)\phi} + 5 \times 10^4 \xi (\rho C_p)_s \sqrt{\frac{k_B T}{\rho_s D}} f(T, \phi) \quad (8)$$

where  $\xi$  and  $k_B$  are respectively, related to particle motion and Stefan- Boltzmann constant. The function  $f(T, \phi)$  can vary continuously with particle volume fraction as  $f(T, \phi) = (-6.04\phi + 0.4705)T + (1722.30\phi - 134.63)$ . Comparing equation (6) with equation (8), it is realized that the first part of equation (8) is a special case with sphericity 1 of equation (6). To tackle the



effect of heat transfer, sphericity and temperature dependent Brownian motion of  $Cu$  and  $Al_2O_3$  nanofluids, equation (8) is modified to take the form

$$\frac{k_{nf}}{k_f} = \frac{k_s + (n-1)k_f + (n-1)(k_s - k_f)\phi}{k_s + (n-1)k_f - (k_s - k_f)\phi} + 5 \times 10^4 \xi \phi (\rho C_p)_s \sqrt{\frac{k_B T}{\rho_s D}} f(T, \phi) \quad (9)$$

## 2. DIMENSIONAL ANALYSIS

To effectively tackle the governing fluid flow equations, dimensional homogeneity of the governing equations using the Buckingham- $\pi$  theorem is stated

$$u = \frac{v_r t'}{D}, r = \frac{r'}{D}, (\text{Re}^{-1}) = \frac{\mu_f}{v_r \rho_f D}, \theta = \frac{T - T_0}{T_0 - T_w}, \text{Pr} = \frac{v_r (\rho C_p)_f}{k_f}, G_\theta = \frac{g \beta_f (T - T_0) \mu_f}{v_r^3}$$

Also, substitute equation (9) into equation (2) and equation (5) into equation (1), the resulting equations transformed into

$$\frac{(1 + a\phi + b\phi^2)}{\text{Re}} \left( \frac{2u}{r^2} + \frac{4}{r} \frac{\partial u}{\partial r} + \frac{\partial^2 u}{\partial r^2} \right) + \left( (1 - \phi) + \phi \frac{\beta_s}{\beta_f} \right) G_\theta \theta = 0 \quad (10)$$

$$\frac{\delta}{\text{Pr}} \left( \frac{2}{r} \frac{\partial \theta}{\partial r} + \frac{\partial^2 \theta}{\partial r^2} \right) = 0 \quad (11)$$

Subject to the boundary conditions

$$\begin{aligned} u|_{r=1} &= 0 \\ u|_{r=0} &= 0 \end{aligned} \quad (12)$$

$$\begin{aligned} \theta|_{r=1} &= 1 \\ \theta|_{r=0} &= 0 \end{aligned} \quad (13)$$

where  $\text{Re}$  is Reynolds' number,  $\text{Pr}$  is Prandtl number,  $G_\theta$  is Grashofs number,  $\theta$  is dimensionless temperature,  $\mathbf{u}$  is dimensionless velocity and  $\mathbf{r}$  is dimensionless radius of the nanoparticles.

$$\delta = \frac{k_s + (n-1)k_f + (n-1)(k_s - k_f)\phi}{k_s + (n-1)k_f - (k_s - k_f)\phi} + 5 \times 10^4 \xi \phi (\rho C_p)_s \sqrt{\frac{k_B \theta}{\rho_s D}} f(T, \phi)$$

Simplification of equation (11) results in

$$\frac{\left( \alpha_1 + 5 \times 10^4 \xi \phi (\rho C_p)_s \sqrt{\frac{k_B}{\rho_s D}} \left( (-6.04\phi + 0.4705)\theta^{1.5} + (1722.3\phi - 134.63)\theta^{0.5} \right) \right)}{\text{Pr}} \left( \frac{2}{r} \frac{\partial \theta}{\partial r} + \frac{\partial^2 \theta}{\partial r^2} \right) = 0 \quad (14)$$

$$\text{where } \alpha_1 \text{ Pr} = \frac{k_s + (n-1)k_f + (n-1)(k_s - k_f)\phi}{k_s + (n-1)k_f - (k_s - k_f)\phi}$$

### Method of Solution

Approximate  $\theta^{1.5}$  and  $\theta^{0.5}$  using Taylor's series expansion about 1 and neglect powers of  $\theta \geq 2$  and simplify, equation (14) can be written as

$$(\alpha_1 + a_1(3\theta - 1) + a_2(\theta + 1)) \left( \frac{2}{r} \frac{\partial \theta}{\partial r} + \frac{\partial^2 \theta}{\partial r^2} \right) = 0 \quad (15)$$

where

$$a_1 = \frac{\left( 5 \times 10^4 \xi \phi (\rho C_p)_s \sqrt{\frac{k_B}{\rho_s D}} (-6.04\phi + 0.4705) \right)}{2 \text{ Pr}}$$

$$a_2 = \frac{\left( 5 \times 10^4 \xi \phi (\rho C_p)_s \sqrt{\frac{k_B}{\rho_s D}} (1722.3\phi - 134.63) \right)}{2 \text{ Pr}}$$

The simplification of equation (15) and its solution as well as imposing the boundary conditions of equation (13), results in

$$\theta^2(3a_1 + a_2) + \theta(\alpha_1 - a_1 + a_2) - (\alpha_1 + 2a_1 + 2a_2)r = 0 \quad (16)$$

and finally reduced to

$$\theta(r) = \frac{-(\alpha_1 - a_1 + a_2) \pm \sqrt{(\alpha_1 - a_1 + a_2)^2 + 4(3a_1 + a_2)(\alpha_1 + 2a_1 + 2a_2)r}}{2(3a_1 + a_2)} \quad (17)$$

Since  $\theta > 0$ ,  $+\theta$  is chosen.

To solve equation (10), equation (17) is put into it and the resulting expression is simplified as

$$\left( \frac{2u}{r^2} + \frac{4}{r} \frac{\partial u}{\partial r} + \frac{\partial^2 u}{\partial r^2} \right) + \beta_1 \left( \frac{\beta_2 + \sqrt{\beta_2^2 + \beta_3 r}}{\beta_4} \right) = 0 \quad (18)$$

The resulting solution of equation (18), after imposing the boundary conditions of equation (13) is given as

$$u(r) = \frac{\beta_1 r^2}{2\beta_4} - \frac{4(\sqrt{\beta_2^2 + \beta_3 r})^5}{15\beta_4\beta_3^2} + \left( \frac{4(\sqrt{\beta_2^2 + \beta_3 r})^5}{15\beta_4\beta_3^2} - \frac{1}{2} \right) r + \frac{4(\sqrt{\beta_2^2})^5}{15\beta_4\beta_3^2} \quad (19)$$

where



$$\beta_1 = \frac{\left( (1-\phi) + \phi \frac{\beta_s}{\beta_f} \right) \text{Re } G_\theta}{(1+a\phi+b\phi^2)}, \quad \beta_2 = (\alpha_1 - a_1 + a_2), \quad \beta_3 = 4(3a_1 + a_2)(\alpha_1 + 2a_1 + 2a_2), \quad \beta_4 = 2(3a_1 + a_2)$$

The mass flux  $\varpi$  and the mean temperature  $\theta_m$  are obtained by evaluating the integral

$$\varpi = \int_0^1 u(r) dr \quad (20)$$

and

$$\theta_m = \frac{\int_0^1 u(r)\theta(r) dr}{\int_0^1 u(r) dr} \quad (21)$$

### Heat Transfer Coefficient (Nu)

It has been shown that the heat transfer performance is a better indicator than the effective thermal conductivity of nanofluids, particularly when such nanofluids are used as coolants and other functions in industries. This property necessitated the formation of nanofluid models to either complement the models of thermal conductivity or an improved determination of effective thermal conductivity. Following the models for determining the heat transfer coefficients of nanofluids (Polidori et al [25], Mansour et al [26]), the mean Nusselt number is calculated thus,

$$\left. \frac{\partial \theta(r)}{\partial r} \right|_{r=0} = Nu = \frac{\beta_3}{2\beta_4 \sqrt{\beta_2^2}} \quad (20)$$

### Skin Friction

The skin friction is given by

$$\left. \frac{\partial u(r)}{\partial r} \right|_{r=0} = \tau = \frac{2\beta_3}{3\beta_4 \beta_3^2 (\sqrt{\beta_2^2})^3} + \left( \frac{4(\sqrt{\beta_2^2 + \beta_3})^5}{15\beta_4 \beta_3^2} - \frac{1}{2} \right) \quad (21)$$

## 3. RESULTS AND DISCUSSION

### Results

**Table 4:** Numerical values of mean Nusselt number for various values of Prandtl number in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} \text{ JK}^{-1}, \quad \xi = 1, \quad \theta = 25, \quad d = 15 \text{ nm}, \quad \phi = 0.06 \text{ mm}^3$$

Pr	$Nu(Al_2O_3)C_2H_6O_2$	$Nu(Al_2O_3)H_2O$	$Nu(Cu)C_2H_6O_2$	$Nu(Cu)H_2O$
0.71	$-3.60599 \times 10^{-12}$	$-3.48063 \times 10^{-12}$	$2.07758 \times 10^{-12}$	$2.06972 \times 10^{-12}$

1.71	$-3.60597 \times 10^{-12}$	$-3.48062 \times 10^{-12}$	$2.07757 \times 10^{-12}$	$2.06971 \times 10^{-12}$
2.71	$-3.60593 \times 10^{-12}$	$-3.48058 \times 10^{-12}$	$2.07756 \times 10^{-12}$	$2.06969 \times 10^{-12}$
3.71	$-3.60588 \times 10^{-12}$	$-3.48053 \times 10^{-12}$	$2.07753 \times 10^{-12}$	$2.06967 \times 10^{-12}$

**Table 5:** Numerical values of mean Nusselt number for various values of nanoparticles volume fractions in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15nm, Pr = 0.71$$

$\phi(mm^3)$	$Nu(Al_2O_3)C_2H_6O_2$	$Nu(Al_2O_3)H_2O$	$Nu(Cu)C_2H_6O_2$	$Nu(Cu)H_2O$
0.06	$3.60599 \times 10^{-12}$	$3.48063 \times 10^{-12}$	$2.07758 \times 10^{-12}$	$2.06972 \times 10^{-12}$
0.07	$9.80488 \times 10^{-13}$	$9.41793 \times 10^{-13}$	$5.6575 \times 10^{-13}$	$5.63316 \times 10^{-12}$
0.08	$1.65227 \times 10^{-13}$	$1.57965 \times 10^{-13}$	$9.54736 \times 10^{-14}$	$9.50156 \times 10^{-14}$
0.09	$5.51207 \times 10^{-12}$	$5.24614 \times 10^{-12}$	$3.18945 \times 10^{-12}$	$3.17262 \times 10^{-12}$

**Table 6:** Numerical values of mean Nusselt number for various values of nanoparticles diameter in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, \phi = 0.06mm^3, Pr = 0.71$$

$d(nm)$	$Nu(Al_2O_3)C_2H_6O_2$	$Nu(Al_2O_3)H_2O$	$Nu(Cu)C_2H_6O_2$	$Nu(Cu)H_2O$
15	$3.60599 \times 10^{-12}$	$3.48063 \times 10^{-12}$	$2.07758 \times 10^{-12}$	$2.06972 \times 10^{-12}$
17	$4.08679 \times 10^{-12}$	$3.94472 \times 10^{-12}$	$2.35459 \times 10^{-12}$	$2.34568 \times 10^{-12}$
19	$4.56759 \times 10^{-12}$	$4.4088 \times 10^{-12}$	$2.6316 \times 10^{-12}$	$2.62164 \times 10^{-12}$
21	$5.04838 \times 10^{-12}$	$4.87289 \times 10^{-12}$	$2.90861 \times 10^{-12}$	$2.8976 \times 10^{-12}$

**Table 7:** Numerical values of mean Nusselt number for various values of nanoparticles Sphericity in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, \phi = 0.06mm^3, Pr = 0.71, d(nm) = 15$

$\psi$	$Nu(Al_2O_3)C_2H_6O_2$	$Nu(Al_2O_3)H_2O$	$Nu(Cu)C_2H_6O_2$	$Nu(Cu)H_2O$
0.36	$4.47397 \times 10^{-12}$	$4.19821 \times 10^{-12}$	$2.60158 \times 10^{-12}$	$2.58334 \times 10^{-12}$
0.52	$3.60599 \times 10^{-12}$	$3.48063 \times 10^{-12}$	$2.07758 \times 10^{-12}$	$2.06972 \times 10^{-12}$
0.62	$3.31023 \times 10^{-12}$	$3.22403 \times 10^{-12}$	$1.90174 \times 10^{-12}$	$1.89643 \times 10^{-12}$
0.81	$2.96389 \times 10^{-12}$	$2.91493 \times 10^{-12}$	$1.69762 \times 10^{-12}$	$1.69467 \times 10^{-12}$





**Table 8:** Numerical values of Skin friction for various values of Prandtl number in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $d = 15nm$ ,  $\phi = 0.06mm^3$

$Pr$	$\tau (Al_2O_3)C_2H_6O_2$	$\tau (Al_2O_3)H_2O$	$\tau (Cu)C_2H_6O_2$	$\tau (Cu)H_2O$
0.71	$-1.70014 \times 10^{17}$	$-1.61226 \times 10^{17}$	$-4.01659 \times 10^{17}$	$-3.99391 \times 10^{17}$
1.71	$-8.7099 \times 10^{14}$	$-8.25961 \times 10^{14}$	$-2.05783 \times 10^{15}$	$-2.04616 \times 10^{15}$
2.71	$-5.47952 \times 10^{13}$	$-5.194 \times 10^{13}$	$-1.29578 \times 10^{14}$	$-1.28839 \times 10^{14}$
3.71	$-8.00715 \times 10^{12}$	$-7.55025 \times 10^{12}$	$-1.91401 \times 10^{13}$	$-1.90237 \times 10^{13}$

**Table 9:** Numerical values of skin friction for various values of nanoparticles volume fractions in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15nm, Pr = 0.71$$

$\phi(mm^3)$	$\tau (Al_2O_3)C_2H_6O_2$	$\tau (Al_2O_3)H_2O$	$\tau (Cu)C_2H_6O_2$	$\tau (Cu)H_2O$
0.06	$-1.70014 \times 10^{17}$	$-1.61226 \times 10^{17}$	$-4.01659 \times 10^{17}$	$-3.99391 \times 10^{17}$
0.07	$-1.58285 \times 10^{18}$	$-1.49008 \times 10^{18}$	$-3.74798 \times 10^{18}$	$-3.72381 \times 10^{18}$
0.08	$3.00003 \times 10^{19}$	$2.80444 \times 10^{19}$	$7.11892 \times 10^{19}$	$7.06775 \times 10^{19}$
0.09	$2.0286 \times 10^{17}$	$1.88359 \times 10^{17}$	$4.82372 \times 10^{17}$	$4.78561 \times 10^{18}$

**Table 10:** Numerical values of skin friction for various values of nanoparticles diameter in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $\phi = 0.06mm^3$ ,  $Pr = 0.71$

$d(nm)$	$\tau (Al_2O_3)C_2H_6O_2$	$\tau (Al_2O_3)H_2O$	$\tau (Cu)C_2H_6O_2$	$\tau (Cu)H_2O$
15	$-1.70014 \times 10^{17}$	$-1.61226 \times 10^{17}$	$-4.01659 \times 10^{17}$	$-3.99391 \times 10^{17}$
17	$-1.40912 \times 10^{17}$	$-1.33629 \times 10^{17}$	$-3.32914 \times 10^{17}$	$-3.31026 \times 10^{17}$
19	$-1.19255 \times 10^{17}$	$-1.13095 \times 10^{17}$	$-2.81757 \times 10^{17}$	$-2.80159 \times 10^{17}$
21	$-1.02634 \times 10^{17}$	$-9.73293 \times 10^{16}$	$-2.4248 \times 10^{17}$	$-2.41105 \times 10^{17}$

**Table 11:** Numerical values of skin friction for various values of nanoparticles Sphericity in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $\phi = 0.06mm^3$ ,  $Pr = 0.71$ ,  $d(nm) = 15$

$\psi$	$\tau (Al_2O_3)C_2H_6O_2$	$\tau (Al_2O_3)H_2O$	$\tau (Cu)C_2H_6O_2$	$\tau (Cu)H_2O$
--------	---------------------------	----------------------	----------------------	-----------------

0.36	$-2.34957 \times 10^{17}$	$-2.13572 \times 10^{17}$	$-5.62845 \times 10^{17}$	$-5.56934 \times 10^{17}$
0.52	$-1.70014 \times 10^{17}$	$-1.61226 \times 10^{17}$	$-4.01669 \times 10^{17}$	$-3.99391 \times 10^{17}$
0.62	$-1.49532 \times 10^{17}$	$-1.4373 \times 10^{17}$	$-3.51769 \times 10^{17}$	$-3.50299 \times 10^{17}$
0.81	$-1.2669 \times 10^{17}$	$-1.23563 \times 10^{17}$	$-2.96682 \times 10^{17}$	$-2.95911 \times 10^{17}$

**Table 12:** Numerical values of Thermal conductivity ratio for various values of nanoparticles volume fractions in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15nm, Pr = 0.71$$

$\phi(mm^3)$	$\frac{k_{nf}}{k_f} (Al_2O_3) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Cu) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Cu) H_2O$	$\frac{k_{nf}}{k_f} (Al_2O_3) H_2O$
0.06	-29.9320	-29.9246	-30.2434	-30.2472
0.07	-12.6446	-12.6358	-13.0116	-13.0162
0.08	4.64418	4.65451	4.22025	4.21494
0.09	21.9344	21.9462	21.4523	21.4462

**Table 13:** Computed values of Thermal conductivity ratio for various values of nanoparticles Temperature in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \phi = 0.06mm^3, d = 15nm, Pr = 0.71$$

$\theta$	$\frac{k_{nf}}{k_f} (Cu) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Al_2O_3) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Cu) H_2O$	$\frac{k_{nf}}{k_f} (Al_2O_3) H_2O$
25	-29.9246	-29.932	-30.2434	-30.2472
50	-29.9246	-29.932	-30.2434	-30.2472
100	-29.9246	-29.932	-30.2434	-30.2472
1000	-29.9244	-29.9318	-30.2432	-30.2470



**Table 14:** Numerical values of Thermal Conductivity ratio for various values of nanoparticles diameter in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, \phi = 0.06 mm^3, Pr = 0.71$$

$d(nm)$	$\frac{k_{nf}}{k_f} (Al_2O_3) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Cu) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Cu) H_2O$	$\frac{k_{nf}}{k_f} (Al_2O_3) H_2O$
15	-29.932	-29.9246	-30.2434	-30.2472
17	-29.932	-29.9246	-30.2434	-30.2472
19	-29.932	-29.9246	-30.2434	-30.2472
21	-29.932	-29.9246	-30.2434	-30.2472

**Table 15:** Numerical values of Thermal conductivity ratio for various values of sphericity in  $C_2H_6O_2$  and  $H_2O$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15 nm, \phi = 0,06 mm^3 Pr = 0.71$$

$\psi$	$\frac{k_{nf}}{k_f} (Al_2O_3) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Cu) C_2H_6O_2$	$\frac{k_{nf}}{k_f} (Al_2O_3) H_2O$	$\frac{k_{nf}}{k_f} (Cu) H_2O$
0.36	-29.7771	-29.7618	-29.8246	-29.7672
0.52	-29.9320	-29.9246	-29.9559	-29.9272
0.62	-29.9890	-29.9837	-30.0061	-29.9856
0.81	-30.0590	-30.0559	-30.0693	-30.057

**Table 16:** Numerical values of Temperature profile for various values of nanoparticles volume fractions in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15 nm, Pr = 0.71$$

$\phi(mm^3)$	$\theta(r) (Al_2O_3) C_2H_6O_2$	$\theta(r) (Al_2O_3) H_2O$	$\theta(r) (Cu) C_2H_6O_2$	$\theta(r) (Cu) H_2O$
0.06	$3.65787 \times 10^{-21}$	$3.65787 \times 10^{-21}$	$2.11613 \times 10^{-21}$	$2.11513 \times 10^{-21}$
0.07	$9.29939 \times 10^{-22}$	$9.29939 \times 10^{-22}$	$5.26524 \times 10^{-22}$	$5.26524 \times 10^{-22}$
0.08	$1.52039 \times 10^{-22}$	$1.52039 \times 10^{-22}$	$6.88666 \times 10^{-23}$	$9.18222 \times 10^{-23}$
0.09	$4.20135 \times 10^{-21}$	$4.3694 \times 10^{-21}$	$2.41049 \times 10^{-21}$	$2.53735 \times 10^{-21}$



**Table 17:** Numerical values of Temperature profile for various values of Prandtl number in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $d = 15nm$ ,  $\phi = 0.06mm^3$

$Pr$	$\theta(r)$ $(Al_2O_3)C_2H_6O_2$	$\theta(r) (Al_2O_3) H_2O$	$\theta(r) (Cu) C_2H_6O_2$	$\theta(r) (Cu) H_2O$
0.71	$3.65787 \times 10^{-21}$	$3.65987 \times 10^{-21}$	$2.11514 \times 10^{-21}$	$2.11513 \times 10^{-21}$
1.71	$2.13685 \times 10^{-20}$	$2.9941 \times 10^{-20}$	$1.21694 \times 10^{-20}$	$1.22402 \times 10^{-20}$
2.71	$5.37676 \times 10^{-20}$	$7.52176 \times 10^{-20}$	$3.0611 \times 10^{-20}$	$3.0611 \times 10^{-20}$
3.71	$1.0055 \times 10^{-19}$	$1.40866 \times 10^{-19}$	$5.74104 \times 10^{-20}$	$5.74104 \times 10^{-20}$

**Table 18:** Numerical values of Temperature profile for various values of nanoparticles diameter in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15nm, Pr = 0.71$$

$d(nm)$	$\theta(r) (Al_2O_3) C_2H_6O_2$	$\theta(r) (Al_2O_3) H_2O$	$\theta(r) (Cu) C_2H_6O_2$	$\theta(r) (Cu) H_2O$
15	$3.65787 \times 10^{-21}$	$3.65787 \times 10^{-21}$	$2.11513 \times 10^{-21}$	$2.11513 \times 10^{-21}$
17	$4.22552 \times 10^{-21}$	$4.14266 \times 10^{-21}$	$2.37682 \times 10^{-21}$	$2.37682 \times 10^{-21}$
19	$4.64235 \times 10^{-21}$	$4.64235 \times 10^{-21}$	$2.64499 \times 10^{-21}$	$2.64499 \times 10^{-21}$
21	$5.15683 \times 10^{-21}$	$5.15683 \times 10^{-21}$	$2.91976 \times 10^{-21}$	$2.64499 \times 10^{-21}$

**Table 19:** Numerical values of Temperature profile for various values of nanoparticles Sphericity in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $\phi = 0.06mm^3$ ,  $Pr = 0.71$ ,  $d(nm) = 15$

$\psi$	$\theta(r)$ $(Al_2O_3) C_2H_6O_2$	$\theta(r) (Al_2O_3) H_2O$	$\theta(r) (Cu) C_2H_6O_2$	$\theta(r) (Cu) H_2O$
0.36	$3.7357 \times 10^{-21}$	$3.7351 \times 10^{-21}$	$2.11513 \times 10^{-21}$	$2.11513 \times 10^{-21}$
0.52	$3.65787 \times 10^{-21}$	$3.65787 \times 10^{-21}$	$2.11513 \times 10^{-21}$	$2.11513 \times 10^{-21}$
0.62	$3.65787 \times 10^{-21}$	$3.65787 \times 10^{-21}$	$2.11513 \times 10^{-21}$	$2.11513 \times 10^{-21}$
0.81	$3.7357 \times 10^{-21}$	$3.65787 \times 10^{-21}$	$2.11513 \times 10^{-21}$	$2.11513 \times 10^{-21}$



**Table 20:** Numerical values of Velocity profile for various values of nanoparticles volume fractions in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15nm, Pr = 0.71, Re = 1000, G_\theta = 0.92$$

$\phi(mm^3)$	$u(r) (Al_2O_3)C_2H_6O_2$	$u(r) (Al_2O_3)H_2O$	$u(r) (Cu)C_2H_6O_2$	$u(r) (Cu)H_2O$
0.06	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
0.07	$-1.18714 \times 10^{10}$	$-1.11756 \times 10^{10}$	$-2.81099 \times 10^{10}$	$-2.79286 \times 10^{10}$
0.08	$2.25002 \times 10^{11}$	$2.10333 \times 10^{11}$	$5.33919 \times 10^{11}$	$5.30081 \times 10^{11}$
0.09	$1.52145 \times 10^9$	$1.41268 \times 10^9$	$3.61778 \times 10^9$	$3.58919 \times 10^9$

**Table 21:** Numerical values of Velocity profile for various values of Prandtl number in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, d = 15nm, Re = 1000, G_\theta = 0.92$$

$Pr$	$u(r) (Al_2O_3)C_2H_6O_2$	$u(r) (Al_2O_3)H_2O$	$u(r) (Cu)C_2H_6O_2$	$u(r) (Cu)H_2O$
0.71	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
1.71	$-6.53311 \times 10^6$	$-6.19543 \times 10^6$	$-1.54349 \times 10^7$	$-1.53474 \times 10^7$
2.71	-412363	-391048	-974235	-968710
3.71	-62639.7	-59401.9	-147991	-147151

**Table 22:** Numerical values of Velocity profile for various values of nanoparticles diameter in  $H_2O$  and  $C_2H_6O_2$  based fluids when

$$k_B = 1.380658 \times 10^{-23} JK^{-1}, \xi = 1, \theta = 25, Pr = 0.71, Re = 1000, G_\theta = 0.92$$

$d(nm)$	$u(r) (Al_2O_3)C_2H_6O_2$	$u(r) (Al_2O_3)H_2O$	$u(r) (Cu)C_2H_6O_2$	$u(r) (Cu)H_2O$
15	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
17	$-1.05684 \times 10^9$	$-1.00222 \times 10^9$	$-2.4968 \times 10^9$	$-2.4827 \times 10^9$
19	$-8.94446 \times 10^8$	$-8.48214 \times 10^8$	$-2.11319 \times 10^9$	$-2.1012 \times 10^9$
21	$-7.6976 \times 10^8$	$-7.29973 \times 10^8$	$-1.81861 \times 10^9$	$-1.80829 \times 10^9$



**Table 23:** Numerical values of Velocity profile for various values of nanoparticles Sphericity in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $d = 15nm$ ,  $Pr = 0.71$ ,  $Re = 1000$ ,  $G_\theta = 0.92$

$\psi$	$u(r)$ $(Al_2O_3)C_2H_6O_2$	$u(r)$ $(Al_2O_3)H_2O$	$u(r)$ $(Cu)C_2H_6O_2$	$u(r)$ $(Cu)H_2O$
0.36	$-1.76218 \times 10^9$	$-1.6018 \times 10^9$	$-4.22135 \times 10^9$	$-4.17702 \times 10^9$
0.52	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
0.62	$-1.12151 \times 10^9$	$-1.07798 \times 10^9$	$-2.63828 \times 10^9$	$-2.62725 \times 10^9$
0.81	$-9.50177 \times 10^8$	$-9.26728 \times 10^8$	$-2.22512 \times 10^9$	$-2.21934 \times 10^9$

**Table 24:** Numerical values of Velocity profile for various values of Reynolds' number in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $d = 15nm$ ,  $Pr = 0.71$ ,  $G_\theta = 0.92$

$Re$	$u(r)$ $(Al_2O_3)C_2H_6O_2$	$u(r)$ $(Al_2O_3)H_2O$	$u(r)$ $(Cu)C_2H_6O_2$	$u(r)$ $(Cu)H_2O$
1000	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
2000	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
3000	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
4000	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$

**Table 25:** Numerical values of Velocity profile for various values of Grashofs number in  $H_2O$  and  $C_2H_6O_2$  based fluids when  $k_B = 1.380658 \times 10^{-23} JK^{-1}$ ,  $\xi = 1$ ,  $\theta = 25$ ,  $d = 15nm$ ,  $Pr = 0.71$ ,  $Re = 1000$ ,

$G_\theta$	$u(r)$ $(Al_2O_3)C_2H_6O_2$	$u(r)$ $(Al_2O_3)H_2O$	$u(r)$ $(Cu)C_2H_6O_2$	$u(r)$ $(Cu)H_2O$
0.92	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
1.92	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
2.92	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$
4000	$-1.27511 \times 10^9$	$-1.2092 \times 10^9$	$-3.01253 \times 10^9$	$-2.99544 \times 10^9$



**Table 26:** Computed values of Viscosity ratio of different shapes nanoparticles for various values of nanoparticles volume fractions

$\phi(mm^3)$	Platelet	Blade	Cylinder	Brick
0.06	5.43136	2.31988	5.06584	2.81104
0.07	6.59874	2.62617	6.37656	3.44286
0.08	7.88864	2.95712	7.86816	4.16896
0.09	9.30106	3.31273	9.54064	4.98934

## 4. DISCUSSION

### Mean Nusselt number

Table 4 displayed the effect of Prandtl number on the heat transfer coefficient of Cu and  $Al_2O_3$  nanoparticles in  $H_2O$  and  $C_2H_6O_2$  based fluids. It shows that increase in Pr, corresponds to an increase in the nanofluids of Cu and  $Al_2O_3$  in both  $H_2O$  and  $C_2H_6O_2$ . However, the magnitude of the nanofluid of Cu is greater than nanofluid of  $Al_2O_3$ . Table 5, numerically showed that increase in nanoparticles volume fractions, enhanced the heat transfer coefficient of the nanoparticles in the two base fluids under consideration and this observation is consistent with the work of Polidori et al [26] and Abu-Nada [27]. The nanoparticles diameter is an important parameter in the enhancement of heat transfer coefficient and this fact is clearly demonstrated in Table 6. Almost all literature cited, established this fact. Increase in nanoparticles sphericity as depicted in Table 7, showed a decrease in the heat transfer coefficient. This is because mixture of nanoparticles with base fluids delayed diffusion and this in turn affect the Nusselt number.

### Skin friction

Table 8, displayed that, as the Prandtl number increases, the skin friction within the nanofluids of Cu and  $Al_2O_3$  in  $H_2O$  and  $C_2H_6O_2$  base fluids increases. However,  $Al_2O_3$  nanofluid increase in magnitude appreciates better than Cu nanofluid.

Table 9, showed that the skin friction increases as the nanoparticle volume fraction increases but beyond  $0.08mm^3$  fraction, a decrease was observed. The explanation is that to improve the skin friction of nanofluids particularly Cu and  $Al_2O_3$  nanofluids, care must be taken to ensure the choice of the nanoparticle volume fractions. It is a truism that increase in skin friction between molecules nanofluids is enhanced by the size of the nanoparticles and Table 10 described it vividly in the two nanofluids under consideration.

The skin friction increases as a result of increase in the sphericity of nanoparticles in the nanofluids. However, the increase is higher in water based fluids as shown in Table 11. This observation is consistent with the work of Temovera et al [28].

### Thermal conductivity ratio

Table 12 displayed the effect of increasing nanoparticle volume fractions on thermal conductivity of Cu and  $Al_2O_3$  nanofluids. It shows that increase in volume fractions led to an increase in both the water and ethylene glycol based fluids. This result is in agreement with that of Lee and Choi [29]. Table 13, showed that an increase in temperature up to about 373K does not show any appreciable enhancement in thermal conductivity of Cu and  $Al_2O_3$  nanofluids. This assertion was also corroborated by Li and Williams [30], Kolade et al [31] and Williams et al [32]. However, at temperature of 1273K and above, an increase in thermal conductivity was observed.

An increase in nanoparticles diameter of Alumina and Copper in ethylene glycol and water based fluids as shown in Table 14, no increase in thermal conductivity was observed. From Table 15, an increase in sphericity results in a decrease in thermal conductivity enhancement but the decrease is more pronounced in  $C_2H_6O_2$  based fluid than  $H_2O$  based fluid, Lee and Choi [29] and Wang et al [20] also reported same findings.

### Temperature Profiles

Table 16, showed numerical values which indicated that increasing the volume fractions of Cu and  $Al_2O_3$  nanofluids showed a decrease initially and later an increase in the temperature profile of the nanofluids but increasing the Prandtl number showed a corresponding increase in the temperature profile of the nanofluids as shown in Table 17. Table 18 showed that increasing the diameter of nanoparticles also increases the temperature profile of the nanofluids. A decrease was observed in temperature profile of the nanofluids as the sphericity is increased as shown in Table 19. In the absence of the sphericity, the observations are consistent with the works of Koo and Kleinstrever ([18 and 19]), though weak owing to the presence of Brownian motion

### Velocity Profiles

Tables 20 – 23, respectively displayed the numerical values of increasing volume fractions, Prandtl number, nanoparticles diameter and sphericity of the two nanofluids, showed that the velocity profiles of the nanofluids all increased considerably but surprisingly an increase in Reynolds' number (within the laminar and turbulence flow regime) and Grashof number due to temperature (which implies cooling the surface of the nanofluids) do not affect the velocity profiles of the nanofluids as shown in Table 24 and Table 25 respectively.

Table 26 clearly showed from the model that viscosity is largely dependent on nanoparticle volume fractions and therefore, its increase will no doubt corresponds to an increase in the viscosity of the nanofluids and it is supported by all the models listed in Wang and Mujumdar [33] and the work of Hashin and Shtrikman [34].

## 5. CONCLUSION

The study theoretically tackled thermal conductivity enhancement and heat transfer coefficient of two nanofluids, namely alumina and copper in water and ethylene glycol based fluids. Although, the numerical values used showed considerable agreement with some existing works cited (Xuan and Li [35], Sato et al [36], a departure was also observed (Wong and Leon [37], Kuznetsov and Nield [38]) in others maybe as a result of approach or approximations. One vital observation is that a model however novel may not incorporate all the essential ingredients or factors of a given nanofluid. Temperature is also a weak parameter in influencing the enhancement of thermal conductivity.

### Funding

This study has not received any external funding.

### Conflict of Interest

The authors declare that there are no conflicts of interests.

### Peer-review

External peer-review was done through double-blind method.

### Data and materials availability

All data associated with this study are present in the paper.

## REFERENCE

- Choi S. U. S. Enhancing thermal conductivity of fluids with nanoparticle, in: D.A. Siginer, H.P. Wang (Eds.), *Developments and Applications of Non-Newtonian Flows*. ASME FED. (1995), 66:99–105
- Yu, W. H, France, D. M, Routbort J. L and Choi S. U. S: Review and comparison of nanofluid thermal conductivity and heat transfer enhancements. *Heat Transfer Engineering* 2009, 29:432-460.
- Eapen J, Rusconi R, Piazza R and Yip S: The classical nature of thermal conduction in nanofluids. *Journal of Heat Transfer* 2010, 132, 102402-1-102402-14.
- Kebllinski, P., Eastman, J. A., and Cahill, D. G. Nanofluids for thermal transport. *Materials Today*, (2005). 8(6): 36–44
- Xie H, Wang J, Xi T and Liu Y: Thermal conductivity of suspensions containing nanosized SiC particles. *International Journal of Thermophysics*. 2002, 23(2):571-580.
- Hamilton R. L, Crosser O. K: Thermal conductivity of heterogeneous two component systems. *Industrial Engineering and Chemistry Fundamentals* 1962, 1(3):187-191.
- Jeffrey D. J: Conduction through a random suspension of spheres. *Proceedings of Royal Society, A* 1973, 335: 355-367.



8. Davis R. H: The effective thermal conductivity of a composite material with spherical inclusions. *International Journal of Thermophysics* 1986, 7:609-620.
9. Wang, L. Q, Zhou, X. S, and Wei, X. H: Heat conduction mathematical models and analytical solutions Berlin: Springer-Verlag; 2008.
10. Koo J, Kang Y and Kleinstreuer C. A nonlinear effective thermal conductivity model for carbon nanotube and nanofiber suspensions. *Nanotechnology* 2008, 19, 375705-1-375705-7.
11. Jang S. P and Choi S. U.S: Effects of various parameters on nanofluid thermal conductivity. *ASME Journal of Heat Transfer* 2007, 129:617-623.
12. Patel, H. E., Das, S. K., Sundararagan, T., Nair, A. S., Geoge, B., and Pradeep, T. Thermal conductivities of naked and monolayer protected metal nanoparticle based nanofluids: Manifestation of anomalous enhancement and chemical effects. *Applied Physics Letters*, (2003). 83, 2931–2933
13. Das, S. K., Putta, N., Thiesen, P., and Roetzel, W. Temperature dependence of thermal conductivity enhancement for nanofluids. *ASME Transnational Journal of Heat Transfer*, (2003). 125, 567–574
14. Xuan, Y., Li, Q., and Hu, W. Aggregation structure and thermal conductivity of nanofluids. *AIChE Journal*, (2003). 49(4), 1038–1043
15. Kumar, D. H., Patel, H. E., Kumar, V. R. R., Sundararajan, T., Pradeep, T., and Das, S. K. Model for heat conduction in nanofluids. *Physical Review Letters*, (2004). 93(14): 144,301–1–144,301–4
16. Bhattacharya, P., Saha, S. K., Yadav, A., Phelan, P. E., and Prasher, R. S. Brownian dynamics simulation to determine the effective thermal conductivity of nanofluids. *Journal of Applied Physics*, (2004). 95(11): 6492–6494
17. Putnam, S. A., Cahill, D. G., Braun, P. V., Ge, Z., and Shimmin, R. G. Thermal conductivity of nanoparticle suspensions. *Journal of Applied Physics*, (2006). 99( 8), 084,308
18. Koo, J. and Kleinstreuer, C. A new thermal conductivity model for nanofluids. *Journal of Nanoparticle Research*, (2004), 6(6): 577–588
19. Koo, J. and Kleinstreuer, C. Laminar nanofluid flow in micro-heat sinks. *International Journal of Heat and Mass Transfer*, (2005). 48(13): 2652–2661
20. Wang, X. W, Xu, X. F and Choi, S. U. S: Thermal conductivity of nanoparticle-fluid mixture. *Journal of Thermal physics and Heat Transfer* 1999, 13:474-480.
21. Keblinski P, Phillpot S. R, Choi S. U. S and Eastman J. A: Mechanisms of heat flow insuspensions of nanos-sized particles (nanofluids). *International Journal of Heat and Mass Transfer* 2002, 45:855-863.
22. Tiwari, R. K and Das, M. K. Heat transfer augmentation in a two-sided lid-driven differentially heated square cavity utilizing nanofluids. *International Journal of Heat and Mass Transfer*. (2007). 50; 9-10.
23. Asma, K; Khan, I and Sharidan, S. Exact solution for free convecton flow of nanofluids with ramped wall Temperature. *The European Physical Journal-Plus*. (2015), 130: 57-71.
24. Aaiza, G; Khan I and Shafie S. Energy transfer in mixed convection mhd flow of nanofluid containing different shapes of nanoparticles in a channel filled with saturated porous medium. *Nanoscle Research Letters*. (2015). 10(490): 1-14.
25. Mansour, R. B., Galanis, N., and Nguyen, C. T. Effect of uncertainties in physical properties on forced convection heat transfer with nanofluids. *Applied Thermal Engineering*, (2007). 27(1): 240–249
26. Polidori, G, Fohanno, S, and Nguyen, C. T. A note on heat transfer modelling of Newtonian nanofluids in laminar free convection. *International Journal of Thermal Sciences*, (2007).46(8): 739–744
27. Abu-Nada, E. Application of nanofluids for heat transfer enhancement of separated flows encountered in a backward facing step. *International Journal of Heat and Fluid Flow*, (2008). 29(1): 242–249
28. Timofeeva, E. V; Jules, R. L and Dileep, S Particle Shape effect on Thermo Physical Properties of Alumina Nanofluids. *Journal of Application Physics*. (2009).106: 014304
29. Lee S and Choi S. U. S: Measuring thermal conductivity of fluids containing oxide nanoparticles. *Journal of Heat Transfer* 1999, 121:280-289.
30. Li, C. H, Williams W: Transient and steady-state experimental comparison study of effective thermal conductivity of  $Al_2O_3$ -water nanofluids. *Journal of Heat Transfer* 2008, 130, 042407-1-042407-7.
31. Kolade, B, Goodson K. E and Eaton J. K: Convective performance of nanofluids in a laminar thermally developing tube flow. *Journal of Heat Transfer* 2009, 13: 052402-1-052402-8.
32. Williams, W, Buongiorno J and Hu, L. W: Experimental investigation of turbulent convective heat transfer and pressure loss of alumina/water and zirconia/water nanoparticle colloids (nanofluids) in horizontal tubes. *Journal of Heat Transfer* 2008, 130: 042412-1-042412-7.
33. Wang, X and Mujumdar, A. S. A review on nanofluids - part I: Theoretical and numerical investigations. *Brazilian Journal of Chemical Engineering*. 2008.25(4), 613 - 630
34. Hashin Z and Shtrikman S: Conductivity of polycrystals. *Physical Review* 1963, 130:129-133.
35. Xuan, Y, and Li, Q. Heat transfer enhancement of nanofluids. *International Journal of Heat and Fluid Flow*. 2000, 21: 58-64.
36. Sato, Y, Deutsch, E and Simonin, O. Direct numerical simulations of heat transfer solid particles suspended in

- homogeneous isotropic turbulence. *International Journal of Heat and Fluid Flow*. 1998. 19(2): 187-192
37. Wong, K. V and De Leon, O. Application of Nanofluids: current and future. *Advances in Mechanical Engineering*. 2000. 2: 519659.
38. Kuznetsov, A. V and Nield, D. A. Natural convective boundary layer flow of a nanofluid past a vertical plate. *International Journal of Thermal Science*. 2010. 49: 243-247

